

Boomlift / Manlift

Used Boom Lift Carlsbad - One of the commonest types of industrial equipment and aerial equipment is the boom lift. Also referred to as elevating work platforms, aerial devices, cherry pickers, mobile elevating work platforms and aerial work platforms, boom lifts are capable of completing jobs at higher elevations easily and efficiently. Warehouses, companies, contractors and retail operations and more rely on boom lifts on a daily basis. Keeping workers safe as they access conditions in a higher altitude is priceless. There is a wide variety of boom lift models to choose from. Most boom lifts can be successfully run with a single operator. Boom lifts are beloved in the agricultural and orchard industries, used to harvest fruit without requiring a separate ladder, they keep workers much safer since there is not climbing or bucket balancing involved. It can be difficult to secure a ladder on farmland or in orchard settings. Harvesting fruit is much safer and simpler with a boom lift compared to using a ladder. Gaining Access Over Obstacles Some boom lift models can move up and over obstacles, making them ideal for working over top of items safely and efficiently. Having the capacity to reach an object even when you are unable to maneuver the equipment directly underneath has a variety of applications including window cleaning, telephone pole and line installation and service, fixing overhead cables and numerous other industries. The articulated boom lift is an example that has numerous joints enabling it to bend over or under items. To enable operators to access many places, these sections of the boom lift can move independently. This equipment is popular in narrow storage locations and hallways thanks to its' tight turning radius. Dual-fuel models can work both inside and outside. Diesel versions are best suited outside and electric models are preferred for interior environments.

Articulating Boom Lifts Articulated boom lifts are commonly found on construction sites and used in maintenance applications. They provide a vital piece to the fleet for servicing power lines and overhead wires. Firefighters may use these machines and some articulated boom lifts have water cannons. Telescoping sections are available on certain models to extend reach to the maximum. There are articulating boom lifts complete with an additional jib that allows the platform to extend an extra 6 feet in any direction. Since these machines commonly work on steep ground and rough terrain, they resemble "spiders" with their long legs, and often go by that nickname on the job site. Interior articulating boom lifts are smaller and able to fit through doorways for use inside storage, warehouse and retail capacities. Interior models are typically electric boom lifts due to their lack of dangerous carbon monoxide exhaust and quieter features. Telescopic Boom Lifts Telescopic boom lifts do not bend the way articulating boom lifts do. These units use hydraulics to retract and extend outwards and upwards. The operator who is situated in the platform has the controls to operate and extend the lift on their own. Some taller and larger models have a jib situated near the top that is similar to an articulating boom lift model. Some models of boom lifts can achieve a reach of more than 180 feet. In less than a minute, some models can reach their full extended height since these machines are so stable and reliable. Adjustable speed, along with varying weight range capacities from 500 to 1000 lbs. are available in dual-fuel and diesel options. Available in 4WD and the ability to fit through small spaces. Telescopic booms are common in a variety of settings due to their ability to combine height and reach. Jib Boom lifts that have an extension between the platform and the end of the primary boom are called the jib. This design facilitates an extra hinge or articulation point to enable the platform to move up and down or horizontally. Jibs are an option on many telescoping and articulating boom lifts. There is an articulation point available on certain models situated halfway between the platform and the wheels to allow the machine to reach over an obstacle and be lowered again if needed. Genie Articulating Boom Lifts The Genie Z-boom model is a common kind of articulating boom lift that can be found on the market. Designed to provide the most versatility in difficult to access spaces, this model has the capacity to lift up, over and out with superior positioning. The first articulating Genie Z-30/20 boom was launched in 1985. These machines became immediately popular with their up-and-over design that continues to make them sought after nowadays.

Proper Safety Measures Safety is the utmost priority when operating any kind of boom lift. It is essential that all potential safety hazards are known to anyone working within the area to maintain a safe atmosphere. Safe operation of the machine and personal safety must be paramount. Before operating the machine, effective communication and essential safety gear need to be in place. Be aware of any battery gases, engine fuels, combustible items, lit cigarettes or open flames near the machine and do not operate if any flammable or combustible items are present. It is important to have an accessible, securely mounted and visible fire extinguisher mounted within the operators' reach. Keep work surfaces and charging stations clean and free from clutter or tools that could puncture the tires or damage the machine or its components. Daily Maintenance Before engaging in activity, it is vital to do a visual inspection and consult the maintenance records to make sure all items are up to date and safe prior to operation. These industrial machines rely on lifting and supportive mechanisms to stabilize the weight. Fasteners, straps and chains must be regularly checked to make sure they are safe working order. It is very dangerous to reuse single use fasteners and other components as they might fail if used beyond their recommendations. It is vital to discard oils and solvents safely and efficiently to prevent contaminating the environment. Workbenches and workshop or garage areas need to have adequate lighting and ventilation. To organize and specify, maintenance is categorized into a variety of subsections including Annual Maintenance, Quarterly Maintenance, Programmed and Commissioning Maintenance Intervals. Maintenance Inspection Report Key components of the boom lift are divided up to categorize the inspection process. Common maintenance categories include Control and Function, Turntable, Booms, Platform, Drive Chassis and Engine. Improperly conducting maintenance can lead to unsafe working conditions, damaged components, reduced performance and ultimately downtime. A large part of keeping the boom lift secure and operational is the maintenance inspection report that ensures the operator is safe and monitors the machine's performance and service. Commissioning refers to a list of one-time maintenance procedures to be complete at 50 hours and at 150 hour intervals. Annual and Quarterly maintenance procedures need to be performed once or multiple times a year. Maintenance procedures are based on the operating hours of the boom lift and programmed maintenance may be conducted during pre-delivery machine preparation. Consult your maintenance manual prior to operating to ensure all oil changes, battery life and fluid levels are primed for success.